

**FLOOR SUPPORT BASES
FOR CAR CHARGERS**



BASIC SERIES

The CTC Basic series of floor bases for car charger is designed for all types of chargers on the market. The innovative design, the robust construction with top quality, durable materials (aluminum with electrostatic painting), as well as its custom configuration according to the customer's requirements, are among the key features that rank it among the best and most dynamic solutions on the market.



INFORMATION

MODEL	BASIC SOUKO	BASIC LOGO	BASIC LOGO SOUCO
CODE	761128	761118	761138
UNIT PACKAGING	1	1	1
INCLUDED IN THE PACKAGING	TORX SCREWDRIVER	TORX SCREWDRIVER	TORX SCREWDRIVER

LIGHTING CONNECTION

POWER SUPPLY	NO	DSP-60-12 (NOT INCLUDED)	DSP-60-12 (NOT INCLUDED)
INPUT VOLTAGE	NO	230V AC	230V AC
OUTPUT VOLTAGE	NO	12V DC	12V DC
FREQUENCY	NO	50Hz	50Hz

BUILT-IN LIGHTING

LOGO	NO	LED TAPE 12V DC, PLEXIGLASS WHITE, GREEN	LED TAPE 12V DC, PLEXIGLASS WHITE, GREEN
------	----	--	--

OPERATING CONDITIONS

OPERATING TEMPERATURE	-30° UP TO 50°	-30° UP TO 50°	-30° UP TO 50°
MOISTURE	-30° UP TO 50°	-30° UP TO 50°	-30° UP TO 50°
MAXIMUM ALTITUDE	<2000m	<2000m	<2000m
PROTECTION	IP44	IP44	IP44

GENERALLY

MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM
MATERIAL OF BASE	STEEL 10mm	STEEL 10mm	STEEL 10mm
COLOR	ELECTROSTATIC PAINTING RAL 7016	ELECTROSTATIC PAINTING RAL 7016	ELECTROSTATIC PAINTING RAL 7016
DIMENSIONS	1500H x 350W x 100D	1500H x 350W x 100D	1500H x 350W x 100D
WEIGHT	25K	25K	25K

BASIC DOUBLE SERIES

The CTC Basic series car charger floor mount is designed for all types of chargers on the market. The innovative design, the robust construction with top quality, durable materials (aluminum with electrostatic painting), as well as its custom configuration according to the customer's requirements, are among the key features that rank it among the best and most dynamic solutions on the market .



INFORMATIONS

MODEL	BASIC DOUBLE SUKO	BASIC DOUBLE LOGO	BASIC DOUBLE LOGO SUKO
CODE	761228	761218	761238
UNIT PACKAGING	1	1	1
INCLUDED IN THE PACKAGING	TORX SCREWDRIVER	TORX SCREWDRIVER	TORX SCREWDRIVER

LIGHTING CONNECTION

POWER SUPPLY	NO	DSP-60-12 (NOT INCLUDED)	DSP-60-12 (NOT INCLUDED)
INPUT VOLTAGE	NO	230V AC	230V AC
OUTPUT VOLTAGE	NO	12V DC	12V DC
FREQUENCY	NO	50Hz	50Hz

BUILT-IN LIGHTING

LOGO	NO	LED TAPE 12V DC, PLEXIGLASS WHITE, GREEN	LED TAPE 12V DC, PLEXIGLASS WHITE, GREEN
------	----	--	--

OPERATING CONDITIONS

OPERATING TEMPERATURE	-30° UP TO 50°	-30° UP TO 50°	-30° UP TO 50°
MOISTURE	-30° UP TO 50°	-30° UP TO 50°	-30° UP TO 50°
MAXIMUM ALTITUDE	<2000m	<2000m	<2000m
PROTECTION	IP44	IP44	IP44

GENERALLY

MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM
MATERIAL OF BASE	STEEL 10mm	STEEL 10mm	STEEL 10mm
COLOR	ELECTROSTATIC PAINTING RAL 7016	ELECTROSTATIC PAINTING RAL 7016	ELECTROSTATIC PAINTING RAL 7016
DIMENSIONS	1500H x 500W x 250D	1500H x 500W x 250D	1500H x 500W x 250D
WEIGHT	25K	25K	25K

F L O O R S U P P O R T B A S E S F O R C A R C H A R G E R S



SIMACOM

91 Pylou & Serron
104 41 Athens, Greece
Tel.: +30 210 5120100
email: sales@simacom.gr
www.ctc-electronic.com